

Safety Cables

REDUNDANT BACKUP SAFETY CABLES

SAFETIES™



Safeties™ are prefabricated consistently at the factory under exacting conditions to make installations quick, safe and secure. Use these cables to secure wall mounted and ceiling mounted objects and equipment to structures to bypass the mounting device.

Safety Cable Kits are produced from load-rated aircraft cable and hardware and come in black, zinc and stainless finishes. The proper method for use is to completely bypass the mounted equipment with a safety cable by securing it to the mounted object and to a structural member and with as little slack as possible.

CAUTION: DO NOT USE AS A PRIMARY SUSPENSION DEVICE.

STANDARD FEATURES:

- ▶ Made from high strength aircraft cable
- ▶ Ends are trimmed for quick attachment
- ▶ Load Rated for predictable installations
- ▶ Closely held length tolerances

OPTIONAL ACCESSORIES:

- ▶ See Rigging Component datasheet

SPECIFICATIONS:

Materials: See table on next page

Finish: Galvanized or Stainless

Color: Black, Clear, Zinc or Stainless finish

Design Factor: 5:1 ratio (Ultimate yield point)

Custom length safety cables also available.

PACKAGE CONTENTS:

See table on next page



Style A

Retaining Washers on Both Sides



Style B

Finished Ends with Thimbles on Both Sides



Style C

Loop with Retaining Washer



Style D

Loop on Both Ends



Style E

Adjustable Safety Cables



Adaptive Technologies Group

1635 E. Burnett Street | Signal Hill, CA 90755 USA
Ph: 562.424.1100 | Fax: 562.424.3520
www.adaptivetechgroup.com



ALWAYS INSTALL SAFETY CABLES

WARNING: Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

Safety Cables

REDUNDANT BACKUP SAFETY CABLES

SAFETIES™

Model #	Length (Loop to Loop) Inches/mm	Indoor	Outdoor	Description QTY & Contents	Material / Color	Light Duty	Med Duty	Static WLL(lbs/kg)	Style
CC-096	8/99	✓		(2) 3/8" Quick Links Adjustable 1' - 8' (1) Eye nut 3/8"	Black Stainless Steel Black		✓	220/99.8	E
CC-096-S	8/99	✓		(2) 3/8" Quick Links Adjustable 1' - 8' (1) Eye nut 3/8"	Silver Galvanized Steel		✓	220/99.8	E
SC-012	12/305	✓		(1) 3/32" diameter 7X7 (2) retaining washer	Silver Galvanized Steel	✓		100/45	A
SC-016-B	16/406	✓		(1) 3/32" diameter 7X7 (2) retaining washer	Black Stainless Steel	✓		100/45	A
SC-018	18/457	✓		(1) 3/32" 7X7 (1) retaining washer	Black Stainless Steel	✓		100/45	C
SC-018-BC	18/457	✓		(1) 3/32" diameter 7X7 (1) retaining washer	Black Stainless Steel	✓		100/45	C
SC-024-BC	24/609	✓		(1) 3/32" diameter 7X7 (1) retaining washer	Black Stainless Steel	✓		100/45	C
SC-025	25/635	✓		(1) 3/32" diameter 7X7 (2) retaining washer	Silver Galvanized Steel	✓		100/45	A
SC-025-B	25/635	✓		(1) 3/32" diameter 7X7 (2) retaining washer	Black Stainless Steel	✓		100/45	A
SC-040	40/1016	✓		(1) 3/32" diameter 7X7 (2) retaining washer	Silver Galvanized Steel	✓		100/45	A
SC-040-BC	40/1016	✓		(1) 3/32" diameter 7X7 (1) retaining washer	Black Stainless Steel	✓		100/45	C
SC-188-18-SS	18"/450	✓	✓	3/16" diameter Wire Rope 7X19 (2) 1/4" Shackle	Stainless Steel		✓	750/ 340	B
SC-188-24-SS	24"/610	✓	✓	3/16" diameter Wire Rope 7X19 (2) 1/4" Shackle	Stainless Steel		✓	750/ 340	B
SC-188-30-SS	30"/762	✓	✓	3/16" diameter Wire Rope 7X19 (2) 1/4" Shackle	Stainless Steel		✓	750/ 340	B
SC-188-48-SS	48"/1220	✓	✓	3/16" diameter Wire Rope 7X19 (2) 1/4" Shackle	Stainless Steel		✓	750/ 340	B
SC-188-72-SS	72"/1830	✓	✓	3/16" diameter Wire Rope 7X19 (2) 1/4" Shackle	Stainless Steel		✓	750/ 340	B
SC-188-96-SS	96"/2438	✓	✓	3/16" diameter Wire Rope 7X19 (2) 1/4" Shackle	Stainless Steel		✓	750/ 340	B

* CUSTOM LENGTHS ARE ALSO AVAILABLE

Adaptive Technologies Group
1635 E. Burnett Street | Signal Hill, CA 90755 USA
Ph: 562.424.1100 | Fax: 562.424.3520
www.adaptivetechologiesgroup.com



ALWAYS INSTALL SAFETY CABLES

WARNING: Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.